

## **In The Claims**

1. (Currently Amended) A data processing system for data received by a broadcast data receiver, said system comprising:

a broadcast data receiver provided for receiving multiple transport streams of digital data which are transmitted from remote locations and may be from different sources, said digital data in each transport stream including a series of packets of data provided with associated codes to indicate the type of data i.e video, audio and/or auxiliary data;

said receiver provided with a plurality of tuners, each of which receives a transport stream of digital data;

said receiver provided with means which allow the selection and combination of packets of data from said multiple transport streams of data multiplexed into a single stream of data in response to control commands;

said selected packets of data combined and further processed to generate video and/or audio and/or auxiliary data therefrom; and

each transport stream of data including transport packets provided with packet identification codes for the packets of data in the stream, and a transport stream identification code ~~[[is]]~~ added to each of the transport packets at a position other than that of the packet identification code so as not to change without changing the packet identification codes and identify and differentiate to allow ~~identification and differentiation of~~ each of the packets of data in terms of the specific stream of data from which they originate, and selection of the appropriate data packets to form the said multiplexed single stream of data received by the receiver, and wherein the addition of the transport stream

identification code allows the differentiation of a packet of data in a first transport stream from any packet of data in a further transport stream which has the same packet identification code.

2. (Cancel)

3. (Cancel)

4. (Previously Presented) A data processing system according to claim 1 wherein the identification codes are generated by re-using existing, superfluous data bits within the existing transport packet syntax said bits replaced by the identification code or codes which identify the streams of data being received.

5. (Canceled)

6. (Previously Presented) A data processing system according to claim 1 wherein the identification codes for the multiple data streams are stored in a memory device and reference to said memory by the receiver allows the identification of each of the data streams with reference to the identification codes accompanying the transmitted data streams.

7. (Currently Amended) A method for generation of a single stream of data for subsequent processing, from multiple transport streams of data, said method comprising the steps of:

simultaneously receiving a number of different transport streams of data via a plurality of tuners in a receiver;

selecting packets of data from said different transport streams in accordance with user and/or receiver selection criteria;

multiplexing said selected packets of data into a single stream of data by said receiver;

allocating a transport stream identification code to each of the received transport streams of data;

allocating a packet identification code to each packet of data;

controlling the selection with reference to the appropriate transport stream identification code for the particular transport stream of data in which the data packet to be selected is located when the selection of a data packet is required;

selecting the required data packet once the appropriate transport stream is identified therefrom with reference to the packet identification code allocated to each of the packets for that transport stream of data;

repeating the steps for each of the data packets required to form the single stream of data and wherein the provision of a transport stream identification code for each transport stream of digital data which is received differentiates packets of data contained in other received transport streams which have the same packet identification code; and

wherein the transport stream identification codes are allocated at a position in the packet other than that of the packet identification code so as not to modify ~~without modifying~~ the packet identification codes.

8. (Previously Presented) A method according to claim 7 wherein the particular data packet is selected from the selected transport stream of data with reference to the packet identification code.
9. (Previously Presented) A method according to claim 7 wherein the selection of the data packet can only be made from the transport stream of data identified by the transport stream identification.